

SPEC SHEET

STANDARD SPECIFICATIONS

DIMENSIONS:

Installed Length: 128"
Maximum Door Opening: 7' 6" *
Headroom Clearance Required: 2"
**Up to 10' with optional 8' or 10' rails*

CARTONS:

Number of Cartons: 2
Carton 1: Dimensions and Contents:
20" x 12" x 10"
882LM Multi-Function Control Panel
893LM 3-Button Remote Control
Garage Door Opener Head
The Protector System® Safety Reversing Sensors
Carton 2: Dimensions and Contents:
10' 4" x 5" x 5"
Assembled Solid-Steel T-Rail (Belt)

SECURITY+ 2.0™ RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light
893LM 3-Button Remote Control
Operating Range: 200' (approximately)
Operating Temperature: -40°F to 150°F
Frequency:
Remote Control: 310, 315 & 390 MHz Tri-Band
Receiver: Frequency Agile on 310, 315 & 390 MHz
Security+ 2.0™ Anti-Burglary Coding

MyQ® RADIO

902-928 MHz
50 Channel FHSS (Frequency Hopping Spread Spectrum)
Provides two-way communication from garage door opener and MyQ enabled accessories
Enables remote closing of garage door with key MyQ accessories
Enables monitoring and control of garage door openers and lighting controls via internet-enabled computer or smartphone*
**Requires LiftMaster® Internet Gateway Accessory Model 828LM*

SECURITY+ 2.0™ ENCRYPTED CONTROLS

882LM Multi-Function Control Panel
Program Remote Controls
Maintenance Alert System

CONVENIENCE / SAFETY

The Protector System Safety Reversing Sensors
Alert-2-Close Unattended Close Operation w/ Select Accessories*
Emergency/Quick Release
Automatic Trolley Reconnect
Down Safety Reverse
Up Safety Stop
Door Open/Beam Obstructed/Lights On
Maintenance Alert System
PosiLock® secure lock system
**Timer-to-close feature requires purchase of 880LM or 881LM control panel and is for sectional doors only, not one piece doors.*

ELECTRICAL SPECIFICATIONS

POWER

Voltage: 120V AC, 60Hz
Wattage: 540 Total System
Current Rating: 4.5A
UL Listings: Yes
Length of Line Cord: 4' (3-prong)

ENERGY EFFICIENCY

Approximately 1 Watt Power in Standby Mode*
Enhanced CFL (Compact Fluorescent) Compatible
**Standby Mode at down limit, work lights off*

LOGIC TYPE

Solid State Microcontroller with Built-in Surge Suppressor

LIGHTING

Number of Bulbs: 2
Maximum Wattage: 100 x 2
Adjustable Time, Solid-State Delay
Enhanced CFL (Compact Fluorescent) Compatible, Max 26 Watts

MECHANICAL SPECIFICATIONS

MOTOR

Horsepower: 1/2
RPM: 1,625
Thermal Protection: Automatic
Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Full Reinforced Drive Belt
Reduction Means: Gear 16:1
Door Linkage: Adjustable Door Arm

ADJUSTMENTS

Force: Electronic/Internal Auto Force
Limit: Internal Electronic

TRAVEL RATE

Approximately 7.0" per second

SHIPPING WEIGHTS

Head: 28 lbs.
Rail: 17 lbs.

MATERIALS

Chassis and Chassis Cover: Steel
Rail: Solid-Steel T
Trolley: Steel

WARRANTY

Lifetime Motor Warranty
Lifetime Belt Warranty
1 Year Parts Warranty

HOMELINK® Compatible (version 4.0 or higher)
w/QuickTrain™ Technology*

**May require an external adapter depending on the model and year of your vehicle. Visit homelink.com for additional information.*

LiftMaster®

The Chamberlain Group, Inc. • 845 Larch Avenue • Elmhurst, IL 60126
LMGDSS8355
Printed in U.S.A. 4/13
© 2013 The Chamberlain Group, Inc.